Maraging Steel

Typical Applications

- Missile casings
- Tooling
- Ordnance mounting blocks
- High performance motorsport components
- Couplings
- Jet engine and helicopter drive shafts
- Load cells
- Landing gear

Product Description

C200 - a maraging alloy steel containing 8.5% cobalt and 3.3% molybdenum. This steel is produced by vacuum arc re-melting to provide high strength although this is still low when compared with other maraging steels, nominally 200 ksi tensile (1380 MPa) with an above average level of toughness. The alloy retains its strength up to 450°C and good notch impact is maintained down to minus 50°C and below. This material may be nitrided. C200 is usually supplied in the annealed condition where the microstructure consists of fine martensite before final heat treatment.

SMITHS

Service. Quality. Value.

Machining & Welding

Maraging steels are usually machined in the annealed condition, however, they can be machined in the maraged condition. Components can be machined close to finished dimensions as the low temperature maraging treatment results in minimal distortion. In addition, the small contraction of approximately 0.05% due to maraging results in good dimensional stability.

C200 steel has good weldability.

Availability

Bar and forgings.

Related Specifications

• UNS K29810

Chemical Composition (weight %)												
	Ni	Со	Мо	Ti	Al	Si	Mn	С	S	Р	Zr	В
Min	18.50	8.50	3.25	0.20	0.10							
Max						0.10	0.10	0.03	0.01	0.01	0.01	0.003

Mechanical Properties (after heat treatment)					
Ultimate Tensile Strength 0.2% Yield Strength	210,000 206,000	psi psi			
Elongation Reduction of Area	12 62	%			
Notch Tensile (K=9.0)	325,000	psi			

Technical Assistance

Our knowledgeable staff backed up by our resident team of qualified metallurgists and engineers, will be pleased to assist further on any technical topic.

UK Service Centre	IS:	Quality & Testing:			
Smiths Chelmsford Smiths Gateshead	0121 728 4940 0117 971 2800	Smiths Leeds Smiths Manchester Smiths Norwich Smiths Nottingham Smiths Redruth Smiths Verwood Main Office	01603 789 878	ISO 9001 Wanagement Systems CERTIFIED	UKAS TESTING 1930

All information in our data sheet is based on approximate testing and is stated to the best of our knowledge and belief. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of trading. © Smiths Metal Centres 2023